

ProJoint[™] Porcelain PRIMER

Page: 1 Compilation date: 15/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ProJoint[™] Porcelain PRIMER

Product code: PP20

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Material used in the construction industry.

1.3. Details of the supplier of the safety data sheet

Company name: Nexus Professional Surfacing Systems

Unit 23 Centre Park

Marston Moor Business Park

- Tockwith
- YO26 7QF

United Kingdom

Tel: 01937 858000

Fax: 0871 4345055

Email: sales@nexusprosystems.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture		
Classification under CLP:	Acute Tox. 4: H302; STOT SE 3: H335; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens.	
	1A: H317	
Most important adverse effects:	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction.	
	Causes serious eye damage. May cause respiratory irritation.	

2.2. Label elements

Label elements:

Hazard statements:	H302: Harmful if swallowed.	
	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H318: Causes serious eye damage.	
	H335: May cause respiratory irritation.	
Signal words:	Danger	
Hazard pictograms:	GHS05: Corrosion	
	GHS07: Exclamation mark	



SAFETY DATA SHEET ProJoint[™] Porcelain PRIMER

Page: 2

Precautionary statements:P280: Wear protective gloves/protective clothing/eye protection/face protection.P301+312: IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell.P302+352: IF ON SKIN: Wash with plenty of water/.P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing.P310: Immediately call a POISON CENTER/doctor/.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PORTLAND CEMENT

Section 4: First aid measures

EINECS	CAS	PBT / WEL	CLP Classification	Percent
266-043-4	65997-15-1	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Dam. 1: H318; STOT SE 3:	10-30%
			H335	

4.1. Description of first aid m	easures
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
	immediately with plenty of soap and water.
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist
	examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water
	to drink immediately. Transfer to hospital as soon as possible.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
	doctor.
4.2. Most important symptom	is and effects, both acute and delayed
Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be pain and redness. The eyes may water profusely. There may be severe
	pain. The vision may become blurred. May cause permanent damage.
Ingestion:	pain. The vision may become blurred. May cause permanent damage. There may be soreness and redness of the mouth and throat. Nausea and stomach
Ingestion:	
	There may be soreness and redness of the mouth and throat. Nausea and stomach

ProJoint[™] Porcelain PRIMER

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust. Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: No data available.

ProJoint[™] Porcelain PRIMER

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PORTLAND CEMENT

Workplace exposure limits:

Workplace exposure limits:			Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	-	-	4mg/m ³	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency. Respiratory
	protective device with particle filter.
Hand protection:	Protective gloves.
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	No data available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Powder	
Odour:	Odourless	
Evaporation rate:	Not applicable.	
Oxidising:	Not applicable.	
Solubility in water:	Not applicable.	
Also soluble in:	No data available.	
Viscosity test method:	No data available.	
Boiling point/range°C:	Not applicable. Melting point/range°C:	Not applicable.
Flammability limits %: lower:	Not applicable. upper:	Not applicable.
Flash point°C:	Not applicable. Part.coeff. n-octanol/water:	Not applicable.
Autoflammability°C:	Not applicable. Vapour pressure:	Not applicable.
Relative density:	Not applicable. pH :	Not applicable.
VOC g/l:	Not applicable.	

ProJoint[™] Porcelain PRIMER

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	: There may be irritation and redness at the site of contact.	
Eye contact:	There may be pain and redness. The eyes may water profusely. There may be severe	
	pain. The vision may become blurred. May cause permanent damage.	
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach	
	pain may occur. There may be difficulty swallowing. There may be vomiting.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Absorption	
	through the lungs can occur causing symptoms similar to those of ingestion.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	
Other information:	No data available.	

ProJoint[™] Porcelain PRIMER

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No further relevant information available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Recovery operations:
 No information available.

 Disposal of packaging:
 No data available.

 NB:
 The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: n/a

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

ProJoint[™] Porcelain PRIMER

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
Legal disclaimer:	H335: May cause respiratory irritation.
	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.